


尺寸

量程	H	L	W	T
lb/inches				
50...250	2.50	2.00	0.50	1/4-28 UNF - 2B
500	3.00	2.00	0.75	1/2-20 UNF - 2B
1,000...3,000	3.00	2.00	1.11	1/2-20 UNF - 2B
5,000; 10,000	4.00	3.00	1.00	3/4-16 UNF - 2B
15,000	5.50	4.00	1.25	1-14 UNS - 2B
20,000	7.00	5.00	2.00	1 1/4 - 12 UNF - 2B
kg/mm (由上述尺寸转换)				
22.68...113.4	63.5	50.8	12.7	1/4-28 UNF - 2B
226.8	76.2	50.8	19.1	1/2-20 UNF - 2B
453.6...1,360.8	76.2	50.8	28.2	1/2-20 UNF - 2B
2,268; 4,535.9	101.6	76.2	25.4	3/4-16 UNF - 2B
6,803.9	139.7	101.6	31.8	1-14 UNS - 2B
9,071.8	177.8	127.0	50.8	1 1/4 - 12 UNF - 2B

技术参数							
相关量程	lb	50; 100; 250	500	1K; 2K; 2.5K; 3K	5K; 10K	15K	20K
产品毛重	kg/lb	0.5 / 1	0.7 / 1.5	1 / 2	1.4 / 3	3 / 6.5	7 / 15
灵敏度	mV/V	3.0 ± 1%					
零位输出	mV/V	± 0.02					
非线性	%	< ± 0.017					
重复性	%	< ± 0.017					
滞后误差	%	< ± 0.017					
蠕变	%	< ± 0.023					
阻抗	Ω	350 ± 7					
额定激励电压	V(DC/AC)	10 (15V 最大)					
绝缘阻抗	GΩ	> 2 [ 50 VDC ]					
正常工作温度范围	°C/°F	-10...40 / 14...104					
安全极限载荷	% of full scale	150					
破坏极限载荷	% of full scale	300					
密封方式		胶封, IP67					



- Exc+ 红
- Sig+ 绿
- Exc- 黑
- Sig- 白
- 屏蔽线

可 选

- 耐高温 120°C [248°F]
- 六线制

可 互 换 产 品

制造商	型号
Vishay Celtron.....	STC-SS
Vishay Revere Transducers.....	9363
Vishay Sensortronics.....	60050