



称重传感器获得:



102EHM2 称重模块的安装底板，承载吊环和平台采用优化结构设计，并采用与传感器相匹配的材料和热处理工艺。自动中心复位，拉向设计，多方位转动。

安装稳定性高，对秤体承载后的变形和由温度引起的变形具有自动调整能力。

尺寸

量程	C	H	H1	H2	L	L1	L2	L3	W	W1	W2	W3
lb/inches												
1,000...5,000	0.56 DIA	5.08	2.95	0.50	9.25	6.25	2.75	4.00	5.00	3.75	2.75	4.00
10,000...25,000	0.81 DIA	7.94	4.84	0.75	12.00	7.50	6.00	8.00	8.00	6.00	6.00	8.00
35,000	0.81 DIA	8.02	4.84	0.75	12.00	7.50	6.00	8.00	8.00	6.00	6.00	8.00
50,000...75,000	0.81 DIA	9.38	5.90	1.00	16.12	11.50	6.50	9.00	12.00	9.50	6.50	9.00
kg/mm (由上述尺寸转换)												
453.6...2,268	14.2 DIA	129.0	74.9	12.7	235.0	158.8	69.9	101.6	127.0	95.3	69.9	101.6
4,535.9...11,339.8	20.6 DIA	201.6	123.0	19.0	304.8	190.5	152.4	203.2	203.2	152.4	152.4	203.2
15,875.7	20.6 DIA	203.8	123.0	19.0	304.8	190.5	152.4	203.2	203.2	152.4	152.4	203.2
22,679.6...34,019.4	20.6 DIA	238.2	149.9	25.4	409.4	292.0	165.1	228.6	304.8	241.3	165.1	228.6

可选

- 不锈钢 102ESM2

可互换产品

制造商	型号
Rice Lake.....	RL1600
Vishay Sensortronics.....	65016-TWA