


CE Ex RoHS IP 68

尺寸

量程	C1	H	H1	L	L1	L2	L3	L4	T
lb/inches									
50,000/ 75,000	0.75	2.00	1.96	8.25	7.25	0.50	0.93	1.80	1/2-14 NPT
kg/mm (由上述尺寸转换)									
22,679.9/ 34,019.8	19.0	50.8	44.7	209.6	184.2	12.7	23.6	45.7	1/2-14 NPT

技术参数

相关量程	lb	50K	75K
产品毛重	kg/lb	5 / 12	6 / 13
灵敏度	mV/V	2.0 ± 0.25%	
零位输出	mV/V	± 0.06	
非线性	%	< ± 0.030	
重复性	%	< ± 0.017	
滞后误差	%	< ± 0.023	
蠕变	%	< ± 0.023	
阻抗	Ω	700 ± 10	
额定激励电压	V(DC/AC)	10 (15V 最大)	
绝缘阻抗	GΩ	> 2 [ 50 VDC ]	
正常工作温度范围	°C/°F	-10...40 / 14...104	
安全极限载荷	% of full scale	150	
破坏极限载荷	% of full scale	300	
密封方式		焊封, IP68	



可 选

- 耐高温 120°C [248°F]
- 六线制
- 合金钢 102FH

可互换产品

制造商	型号
Cardinal.....	DB50000S
Cardinal.....	DB75000S
Rice Lake.....	RLDB50000S
Rice Lake.....	RLDB75000S