


CE RoHS IP 68

尺寸

量程	C1	C2	C3	H	H1	H2	H3	H4	H5	L	R	SR	T
kg/mm													
20,000	47	44	76.1	150	16	21	123	3	27	10	5	130	1/2-14 NPT
30,000	47	44	76.1	150	16	21	123	3	27	10	5	160	1/2-14 NPT
40,000	47	44	76.1	150	16	21	123	3	27	10	5	180	1/2-14 NPT
lb/inches (由上述尺寸转换)													
44,092.5	1.9	1.7	3.0	5.9	0.6	0.8	4.8	0.1	1.1	0.4	0.2	5.1	1/2-14 NPT
66,138.7	1.9	1.7	3.0	5.9	0.6	0.8	4.8	0.1	1.1	0.4	0.2	6.3	1/2-14 NPT
88,184.9	1.9	1.7	3.0	5.9	0.6	0.8	4.8	0.1	1.1	0.4	0.2	7.1	1/2-14 NPT

技术参数

相关量程	kg	20t; 30t; 40t
产品毛重	kg/lb	-
灵敏度	mV/V	2 ± 0.25%
零位输出	mV/V	± 0.02
非线性	%	< ± 0.030
重复性	%	< ± 0.023
滞后误差	%	< ± 0.023
蠕变	%	< ± 0.030
阻抗	Ω	705 ± 5
额定激励电压	V(DC/AC)	15 (18V 最大)
绝缘阻抗	GΩ	> 2 [50 VDC]
正常工作温度范围	°C/°F	-10...40 / 14...104
安全极限载荷	% of full scale	150
破坏极限载荷	% of full scale	300
密封方式		焊封, IP68



可互换产品

制造商	型号
HBM.....	C16