


CE RoHS IP 67

尺寸

量程	C1	C2	C3	H	H1	H2	H3	H4	SR	W	W1
kg/mm											
7,500...22,500	47.0	28.0	65.0	89.0	44.0	17.0	23.0	11.0	80.0	97.0	28.0
30,000...40,000	47.0	39.0	81.0	150.0	75.0	31.0	33.0	13.0	120.0	113.0	39.0
50,000	47.0	44.0	99.0	178.0	89.0	32.0	34.0	17.0	180.0	131.0	44.0
100,000	-	62.0	141.3	178.0	89.0	38.5	38.5	17.0	-	173.3	62.0
150,000	-	76.2	165.1	210.0	105.0	42.7	42.7	20.6	-	197.1	76.2
300,000	-	100.0	165.1	280.0	140.0	55.9	55.9	25.0	-	197.1	100.0
lb/inches (由上述尺寸转换)											
16,534.7...49,604	1.85	1.10	2.56	3.19	1.73	0.67	0.91	0.43	3.15	3.82	1.10
66,138.7...88,184.9	1.85	1.54	3.19	5.91	2.95	1.22	1.30	0.51	4.72	4.45	1.54
110,231.1	1.85	1.73	3.90	7.01	3.50	1.26	1.34	0.67	7.09	5.16	1.73
220,462.3	-	2.44	5.56	7.01	3.50	1.52	1.52	0.67	-	6.82	2.44
330,693.4	-	3.00	6.50	8.27	4.13	1.68	1.68	0.81	-	7.76	3.00
661,386.8	-	3.94	6.50	11.02	5.51	2.20	2.20	0.98	-	7.76	3.94

技术参数

相关量程	kg	7.5t; 22.5t; 30t; 40t; 50t; 100t; 150t; 300t
产品毛重	kg/lb	-
灵敏度	mV/V	2 ± 0.1%
零位输出	mV/V	± 0.02
非线性	%	< ± 0.030
重复性	%	< ± 0.017
滞后误差	%	< ± 0.020
蠕变	%	< ± 0.020
阻抗	Ω	1000 ± 2
额定激励电压	V(DC/AC)	10 (15V 最大)
绝缘阻抗	GΩ	> 2 [ 50 VDC ]
正常工作温度范围	°C/°F	-10...40 / 14...104
安全极限载荷	% of full scale	150
破坏极限载荷	% of full scale	300
密封方式		密封, IP67



- Exc+ 红
- Sig+ 绿
- Exc- 黑
- Sig- 白
- 屏蔽线

可互换产品

制造商 型号  
FLINTEC..... RC3(7.5t~50t)