


尺寸

量程	H	L	W	T
lb/inches				
500...3,000	3.00	2.00	1.11	1/2-20 UNF-2B
5,000	4.00	3.00	1.11	3/4-16 UNF-2B
10,000	4.00	3.00	1.25	3/4-16 UNF-2B
15,000	5.50	4.00	1.25	1-14 UNS-2B
20,000	7.00	5.00	2.00	1 1/4-12 UNF-2B
kg/mm				
300...1,000	76.2	50.8	28.2	M12X1.75
2,000; 3,000	101.6	76.2	28.2	M16X2.00
5,000	101.6	76.2	31.8	M24X2.00
10,000	177.8	125.0	50.8	M30X2.00

技术参数

相关量程	kg/lb	300; 500; 1t / 500; 1K; 1.5K; 2K; 2.5K; 3K	2t; 3t / 5K	5t / -	10t / -	- / 10K	- / 15K	- / 20K
产品毛重	kg/lb	0.8 / 1.8	1.5 / 3.3	1.6 / 3.5	-	1.6 / 3.6	2.9 / 6.4	6.9 / 15.3
灵敏度	mV/V	2.0 ± 1%						
零位输出	mV/V	± 0.06						
非线性	%	< ± 0.023						
重复性	%	< ± 0.030						
滞后误差	%	< ± 0.030						
蠕变	%	< ± 0.030						
阻抗	Ω	400 ± 20						
额定激励电压	V(DC/AC)	10 (15V 最大)						
绝缘阻抗	GΩ	> 2 [50 VDC]						
正常工作温度范围	°C/°F	-10...40 / 14...104						
安全极限载荷	% of full scale	150						
破坏极限载荷	% of full scale	300						
密封方式		焊封, IP68						



可 选

- 耐高温 120°C [248°F]
- 公制和英制螺纹可选
- 六线制

可互换产品

制造商	型号
FLINTEC.....	ULB
HBM.....	RSC*
Rice Lake.....	RL20001HE
Vishay Celtron.....	STCHSS
Vishay Sensortronics.....	60063
Vishay TedeA-Huntleigh.....	.620

* HBM RSC 为胶封