


尺寸

量程	C1	C2	C3	H	H1	H2	H3	H4	L	L1	W
lb/inches											
50,000~65,000	1.00	1.00	0.75	2.99	2.40	2.06	0.28	0.79	10.25	8.50	2.20
100,000~125,000	1.00	1.00	-	2.99	2.40	2.06	0.28	-	10.25	8.50	2.20
kg/mm											
10,000; 15,000	19.0	19.0	16.0	49.3	40.0	30.0	5.7	13.7	220.0	170.0	36.0

技术参数

相关量程	kg/lb	10t; 15t / 50K; 65K; 100K; 125K
产品毛重	kg/lb	9 / 19
灵敏度	mV/V	3.0 ± 0.25%
零位输出	mV/V	± 0.06
非线性	%	< ± 0.030
重复性	%	< ± 0.017
滞后误差	%	< ± 0.023
蠕变	%	< ± 0.023
阻抗	Ω	700 ± 10
额定激励电压	V(DC/AC)	10 (15V 最大)
绝缘阻抗	GΩ	>2 [ 50 VDC ]
正常工作温度范围	°C/°F	-10...40 / 14...104
安全极限载荷	% of full scale	150
破坏极限载荷	% of full scale	300
密封方式		焊封, IP68



可 选

- 耐高温 120°C [248°F]
- 防雷击和大电流
- 六线制
- 不锈钢 102RS

可互换产品

制造商	型号
Rice Lake.....	RL75223
Vishay Revere Transducers.....	5223
Vishay Sensortronics.....	.65040-1127W