



CE RoHS 

尺寸

量程	C1	C2	C3	H	H1	H2	L	SR	W
kg/mm									
100,000	155.0	84.0	95.0	224.0	20.0	18.0	59.0	380.0	191.0
200,000	166.0	120.0	125.0	300.0	39.0	25.0	84.0	450.0	202.0
500,000	268.0	175.0	180.0	425.0	35.0	40.0	127.0	506.0	329.0
lb/inches (由上述尺寸转换)									
220,462.3	6.10	3.31	3.74	12.76	0.79	0.71	2.32	14.96	7.52
440,924.5	6.54	4.72	4.92	11.81	1.54	0.98	3.31	17.72	7.95
1,102,311.3	10.55	6.89	7.09	16.73	1.38	1.57	5.00	19.92	12.95

技术参数

相关量程	kg	100t	200t	500t
产品毛重	kg/lb	9 / 21	20 / 43	77 / 170
灵敏度	mV/V	2 ± 20%		
零位输出	mV/V	± 0.05		
非线性	%	< ± 0.050		
重复性	%	< ± 0.017		
滞后误差	%	< ± 0.017		
蠕变	%	< ± 0.023		
阻抗	$\Omega$	700 ± 5		
额定激励电压	V(DC/AC)	10 (15V 最大)		
绝缘阻抗	G $\Omega$	> 2 [ 50 VDC ]		
正常工作温度范围	°C/°F	-10...40 / 14...104		
安全极限载荷	% of full scale	150		
破坏极限载荷	% of full scale	300		
密封方式		密封, IP67		



- Exc+ 红
- Sig+ 绿
- Exc- 黑
- Sig- 白
- 屏蔽线

可 选

- 耐高温 120°C [248°F]
- 防雷击和大电流
- 六线制