



尺寸

量程	H	L	L1	L2	L3	L4	W	W1	T1	T2
651TA:										
kg/mm										
10...100	40.0	150.0	6.0	19.0	100.0	34.0	29.4	25.4	M6 Depth13	M6 Depth13
lb/inches (由上述尺寸转换)										
22.05...220.46	1.57	5.91	0.23	0.75	3.94	1.34	1.16	1.00	M6 Depth0.51	M6 Depth0.51
651TAUN:										
kg/mm										
10...200	40.0	150.0	6.0	19.0	100.0	34.0	29.4	25.4	1/4-20 UNC Depth13	1/4-28 UNF Depth13
lb/inches (由上述尺寸转换)										
22.05...440.92	1.57	5.91	0.23	0.75	3.94	1.34	1.16	1.00	1/4-20 UNC Depth0.51	1/4-28 UNF Depth0.51

技术参数

相关量程	kg	10; 15; 20; 30	50; 75; 100; 200
产品毛重	kg/lb	0.5 / 1.1	
推荐最大台面尺寸	mm	450×500	
灵敏度	mV/V	2±10%	<ul style="list-style-type: none"> ● Exc+ 红 ● Sig+ 绿 ● Exc- 黑 ● Sig- 白 ● 屏蔽线
零位输出	mV/V	±0.06	
非线性	%	<±0.017	
重复性	%	<±0.017	
滞后误差	%	<±0.017	
蠕变	%	<±0.023	
阻抗	Ω	415±15	
额定激励电压	V(DC/AC)	10 (15V 最大)	
绝缘阻抗	GΩ	>1 [50 VDC]	
正常工作温度范围	°C/°F	-10...40 / 14...104	
安全极限载荷	% of full scale	150	
破坏极限载荷	% of full scale	300	
密封方式		密封胶灌封, IP67	
推荐安装方式		内六角螺钉: 1/4-20UNC-8.8 紧扭力: 6Nm	内六角螺钉: 1/4-20UNC-10.9 紧扭力: 10Nm

可互换产品

制造商	型号
651TAUN	
Mettler-Toledo.....	MT1041
Rice Lake.....	RL1040
Vishay Celtron.....	LOC
Vishay Tedeo-Huntleigh.....	1040
Vishay Tedeo-Huntleigh.....	1041